

Atlas™ Series Hydraulic Presses



The Atlas™ Series Power Presses T25 and T8, are power assisted hydraulic presses operating to 25 Tons and 8 Tons respectively. They have been designed to handle a wide variety of pressing applications, including XRF and IR sample preparation. Both Presses are fully compatible with Specac dies and other sample preparation.

The presses enable the controlled application and release of applied load and can accommodate large samples up to 200mm in diameter. The LCD display shows press status and load conditions giving a digital display of load applied. The power unit is extremely quiet and operates below 62dB(A). Fitted with PETG safety guards as standard The Atlas™ Series Power Presses are fully CE marked to comply with strict European regulations.

The Atlas™ Series Power Presses have a generous working distance of up to 155mm between the pressing faces and are suitable for the preparation of KBr discs for infrared analysis using Specac evacuable pellet dies. They can also be used with heated platens for applications including the preparation of thin polymer film substrates.

The Atlas™ Series Power Presses are durable, easy to use and ideal for repetitive pressing operations at higher loads when used in conjunction with Atlas™ Series Lightweight Dies for x-ray fluorescence sample preparation.

Product Features

- Microprocessor controlled pressure application and release
- Large working distance between pressing surfaces
- Fully CE Marked
- Low noise operation
- Liquid crystal digital display
- Multi-lingual display option
- Integral high clarity PETG safety Guards
- Fully compatible with Specac sample preparation accessories

Specifications T8 T25

Max. Load on Ram (Piston):	8 Tons	25 Tons
Digital Display (0.5 Ton increments)	1 - 8 Ton	
Digital Display (1 Ton increments)		3-25 Ton

Specifications (T8 & T25)

Top Bolster Diameter	32mm
Top Lead Screw Vertical travel	90mm
Ram (Piston) Bolster Diameter	83mm
Ram (Piston) Stroke	24mm
Max/Min Dist. between Pressing Faces	155mm - 40mm
Sample Area (Diameter x Height)	220mm Dia x 155mm
Base Footprint (Width x Depth)	425mm x 405mm
Height (without lead screw)	500mm
Height	545mm - 640mm
Weight	95Kg

Ordering Information T8 T25

UK/Europe (230v, 50Hz)	25400	25420
USA (110v, 60Hz)	25401	25421
Japan (100v, 50/60Hz)	25402	25422

Atlas™ Series Dies

	Max. Load	Part Number
Lightweight 32mm Die	25 Tons	25410
Lightweight 40mm Die	25 Tons	25411

THE SOLUTION IS SPECAC WHAT'S THE PROBLEM?

smiths
A part of Smiths Group plc

Specac

www.specac.com



SPECAC LIMITED,
River House, 97 Cray Ave, St. Mary Cray,
Orpington, Kent BR5 4HE U.K.
Tel : +44 (0)1689 873134
Fax : +44 (0)1689 878527
Registered No. 1008689 England

SPECAC INC.,
410 Creekstone Ridge,
Woodstock, GA 30188 U.S.A.
Toll Free +1 800 447 2558
www.specac.com
Specac is part of Smiths Group plc